

| type number | for width of cable tray (mm) | A (mm) | B (mm) | H (mm) | thickness of metal sheet (mm) | weight (kg/pc) | 🔥 |
|----------------------|------------------------------|--------|--------|--------|-------------------------------|----------------|---|
| NVSO 90x62_S | 62 | 62 | 203 | 12 | 0,55 | 0,12 | 🔥 |
| NVSO 90x62_F | | | | | 0,6 | 0,15 | 🔥 |
| NVSO 90x125_S | 125 | 125 | 203 | 12 | 0,55 | 0,20 | 🔥 |
| NVSO 90x125_F | | | | | 0,8 | 0,35 | 🔥 |
| NVSO 90x250_S | 250 | 250 | 203 | 12 | 0,55 | 0,30 | 🔥 |
| NVSO 90x250_F | | | | | 0,8 | 0,51 | 🔥 |
| NVSO 90x500_S | 500 | 500 | 203 | 15 | 0,70 | 0,93 | 🔥 |
| NVSO 90x500_F | | | | | 0,8 | 1,26 | 🔥 |



product description: This cover is used to cover the rising elbow NSO.
 To fix the cover use 4 pcs of cover fixtures VU or NUV.
 The covers are supplied straight. They are constructed from a single piece of sheet metal with pre-cut sidewalls for subsequent bending during installation.
 These items can also be ordered in a varnished version.

surface finish: S - Pre-Galvanized according to EN 10346, EN 10143, zinc-layer 15-27 µm
 F - Hot Dip Galvanized according to ČSN EN ISO 1461, zinc-layer 45 µm (min. 35 µm)

sales amount: 1 pc

meets the requirements: ČSN EN 61537:02

classification 🔥: ČSN 73 0895P 90-R
 DIN 4102-12E 90
 STN 92 0205PS 90
 Fire classification depends on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire
 🔥 products are approved for non-standard constructions

storage: ČSN EN 60721-3-1

