




type number	width of cable tray	thickness of metal sheet	weight kg/m	amount of bolts for connection
KZI 85X100X0.75_S	100	0,75	1,56	6
KZI 85X100X0.75_F			1,69	
KZI 85X150X0.75_S	150	0,75	1,81	6
KZI 85X150X0.75_F			2,28	
KZI 85X200X0.75_S	200	0,75	2,15	7
KZI 85X200X1.00_S		1,00	2,58	
KZI 85X200X1.00_F		3,01		
KZI 85X300X1.00_S	300	1,00	3,10	7
KZI 85X300X1.00_F			3,60	
KZI 85X400X1.00_S	400	1,00	4,15	8
KZI 85X400X1.00_F			4,83	
KZI 85X500X1.25_S	500	1,25	6,00	8
KZI 85X500X1.25_F			6,79	
KZI 85X600X1.25_S	600	1,25	6,82	8
KZI 85X600X1.25_F			7,78	



height of cable tray: 85 mm

length of cable tray: 3000 mm

product description: Cable tray is designed to create a cable route.

For securing the connection of the trays with the integrated coupling there are used the clamps made from spring steel KSV or the bolts NSM 6X10. To protect the cables, the bolt head is inside the cable tray. A bolt with a GMT surface finish is used for a tray with an F surface finish.

These items can also be ordered in a varnished version.


surface finish: S - Pre-Galvanized according to EN 10346, EN 10143, zinc-layer 15 - 27 µm
 F - Hot Dip Galvanized according to ČSN EN ISO 1461, zinc-layer 45 µm (min. 35 µm)

sales amount: á 3 m

meets the requirements: EN 61537:02








storage: EN 60721-3-1

recycling codes:




DATA SHEET

cable tray with integrated coupling - height 85 mm



The graph show the maximum allowed even loading of the tray in relation to the distances of the supports.



External influences are not taken into account in the permissible load and cannot be burdened by person.

inner usable cross-section of the channel

	KZI	85X100	85X150	85X200	85X300	85X400	85X500	85X600
cross-section (cm ²)	85	127,5	170	255	340	425	510	
CYKY 3X1,5	8,6	57	86	115	172	230	287	345
CYKY 5X1,5	10,1	42	62	83	125	167	208	250
CYKY 3X2,5	9,5	47	71	94	141	188	235	283
CYKY 5X2,5	11,2	34	51	68	102	136	169	203
CYKY 3X4	11,2	34	51	68	102	136	169	203
CYKY 5X4	13,8	22	33	45	67	89	112	134
CYKY 5X6	15,1	19	28	37	56	75	93	112
CYKY 5X10	18	13	20	26	39	52	66	79
CYKY 5X16	20,4	10	15	20	31	41	51	61
CYKY 5X25	26,1	6	9	12	19	25	31	37
CYKY 4X35	24,8	7	10	14	21	28	35	41
CYKY 4X50	31,3	4	7	9	13	17	22	26
CYKY 3X70+50	33,6	4	6	8	11	15	19	23
CYKY 3X95+70	39,3	3	4	6	8	11	14	17
CYKY 3X120+95	43	2	3	5	7	9	11	14
CYKY 3X240+120	56,4	1	2	3	4	5	7	8

The values state the number of cables with the tray at 50% full. Orientation diameters of the cables CYKY. The values are mathematically calculated. The limit values (small tray x big cable or contrariwise) it is necessary to consider combination of the tray and diameter of the cable and used them with reference to technical conditions.